

COVERBIND

CPB2SG

PERFECT BINDER



Item#: 04TPTC5500SMS

Your print shop, in-plant printer, on-demand printer, or bindery can reach new levels of efficiency and convenience with the Coverbind CPB2SG perfect binder with side gluing. This highly productive paperback binding system offers convenient automated actions that are controlled from an LCD panel. Inexpensive to operate, this soft cover binder can be used for short runs with just a couple of books or large jobs with thousands of books. Whatever your need, the Coverbind CPB2SG can help.

Achieve professional perfect back bound books in a snap with this perfect binder system, capable of binding up to 360 books per hour. This fully automated perfect binding system offers automatic/pneumatic clamping, specialized nipping, and essential glue coverage for a secure bind. The CPB2SG also includes a separate, side glue pot, allowing you to control the amount of side glue under a hinge crease. Start binding premium soft cover books, novels, manuals, and more, on-demand with the Coverbind CPB2SG perfect binder with side gluing.

Start binding premium soft cover books, novels, manuals, and more, on-demand with the Coverbind CPB2SG perfect binder with side gluing.

Key Benefits & Features:

- Fast Binding – Bind up to 360 books per hour, depending on the book specifications and operator capabilities. Fast Binding – Bind up to 360 books per hour, depending on the book specifications and operator capabilities.

2 Cddgagclr Amlrpmjq - ? qg knjc amlrpmj n_lcj jcrq wms
asqrm k gxc rfc k_afglc rm wmsp qncagdga hm` osgaijw,

2 ? srm k_rcb Aj_kngle - ? nlcs k_rga nmucpcb aj_kngle
k caf_lgqk q_srm k_rga_jjw _bhsqrq rm wmsp `mmi `jmai
rfgai lcqj sn rm 0+/-2μ,

2 Mnrgk s k Ejsc Nclcrp_rgm1 - Kgjjgle _lb fc_tw+bsrw
lmrfgle ng lq clqspc k_vgk s k ejsc nclcrp_rgm1 dmp dg lgqfcb
`mmi qrpclerf,

2 Qncag_jgxcb Lgnngle - Qcr rfc lgnncp rm npmbasac _l
cvacnrgml_jjw qos_pc+`\_aibc `mmi ugrf _l _bhsqr_`jc fcgefr
_lb bucjj rg kc sn rm 8 qcamlbq,

2 Qrpmlecp @glb - Qgbc ejsgle ml both pc_p, and front md
qnglc k_i cq dmp cvacnrgml_j dg lgqfgle,

2 Q_rsp_rcb Ejsc Amtcp_ec - Ejsgle pmjjcpq q_rsp_rc _lb
pmjjcpq q k mmrf rfc ejsc rm rfc mnrgk s k rfgai lcqj,



Specifications

Maximum Speed	Up to 360 books/hour
Maximum Book Thickness	2.25" (57mm)
Maximum Cover Size	13.4" x 30.75" / 34cm X 78cm
Maximum Spine Length	12.5" (32 cm)
Book Block Size	12.5" x 8.7" / 32cm x 22cm
Display	LCD Screen
Clamp	Automatic/Pneumatic
Roughing Blade	Milling & 2 Heavy Duty Notching Pins
Rollers	2 Glue, 1 Metering & Side Glue Tank
Dimensions (L X W X H)	55" W x 20" D x 42" H
Weight	557 lbs.
Electrical	AC 220-240V, 50-60Hz, 2.9Kw

mybinding.com
1-800-944-4573