

SpotOn® SynPaper for PageWide® XL

Print Media

SpotOn® SynPaper for PageWide® XL is a 4.8 mil (120µ) printable matte white, self-adhesive PP film with a dot patterned, removable pressure sensitive polyacrylate adhesive. The adhesive is protected by a single-sided, siliconized clay coated Kraft release liner. This high quality, ink receptive white synthetic paper was specifically developed for printing with HP PageWide®, but other aqueous and UV inkjet technologies also provide excellent results. SpotOn® SynPaper for PageWide® XL allows for easy, bubble-free application of vibrant graphics.

Typical Applications

- Ideal for short-term (3-6 months) wall and window applications.
- Graphics for seasonal promotional applications and trade show exhibitions.
- Excellent for applications where easy, tool-free installation is necessary.

Print Compatibility

- HP PageWide® XL

Product Structure

Film	Matte White PP	5.3 mil (133µ)
Adhesive	Removable Dot Pattern Polyacrylate	
Release Liner	90 gsm Siliconized 1 Side Bleached Clay Coated Kraft	

Physical Characteristics

Film Thickness	4.8 mil (120µ)
Adhesive Layer	0.5 mil (13µ)
Film/Adhesive Ratio	4.8:0.5
UV Protection Factor	Not Applicable
Outdoor Durability	Not Applicable
Application Temperature	>41°F (5°C)
Service Temperature Range	-4°F to 149°F (-20°C to 65°C)
Shelf Life	1 year
Storage Conditions	64°F to 77°F (18°C to 25°C); 40 - 65% Relative Humidity

Installation Recommendations

Please see SpotOn® installation instructions for further details. The surface must be clean and smooth and free of defects before application.

Recommended Uses

- Mount to boards
- Window graphics
- Temporary sales signage
- CAD documents
- Presentations
- POP
- Event signage
- Grocery store signage
- Variable data posters
- Beverage & food advertisements

IMPORTANT NOTE:

Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein. Only the correct use of the product will allow satisfactory results. For this reason, Drytac is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Drytac at one of the phone numbers listed below.

* PageWide® is a registered trademark of HP.