

ReTac®

Clear PET

ReTac® Clear PET is a clear gloss polyester (PET) film with a ReTac® ultra removable and repositionable adhesive. This high quality, Latex and UV printable clear PET was specifically developed with the environment in mind and is ideal for POP retail and hospitality window, wall, and counter top graphics. Installation is both simple and clean for customers as ReTac Clear PET does not require water to be applied to surfaces. The film also offers residue-free removal, making life easier for customers when an application has reached the end of its life.

- **RETAC CLEAR PET IS APPROVED BY THE US FOOD AND DRUG ADMINISTRATION (FDA) FOR INCIDENTAL FOOD CONTACT, EXTENDING ITS REACH TO PROJECTS INCLUDING COUNTER-TOP GRAPHICS**

PRODUCT CODE: RTZC

3.0
mil

Clear Polyester (PET)



Gloss



Latex UV



Clear ReTac Ultra Removable and Repositionable Adhesive



Widths up to 54 in



INTERIOR & EXTERIOR
(2 Years Removability)

ULTRA REMOVABLE, PVC-FREE GRAPHICS



APPLICATIONS

Counter Top Graphics
Window & Wall Graphics
Retail Promotions
POS Advertising



DRYTAC®
ZERO

MyBinding
When Image Matters.

mybinding.com
1-800-944-4573

ReTac®

Clear PET

ReTac® Clear PET is a 3 mil (75µ) clear printable polyester film coated on one side with ReTac® ultra removable adhesive, protected by a 78# siliconized kraft release paper. ReTac® Clear PET offers a sustainable solution suitable for latex and UV printing, that can be easily applied, re-positioned and removed without surface damage or loss of adhesion.

- **IDEAL FOR EASY TO APPLY RETAIL AND POP WINDOW GRAPHICS, NO WET INSTALL NEEDED**
- **RETAC CLEAR PET IS A NON-PVC SOLUTION, OFFERING A MORE ENVIRONMENTALLY FRIENDLY OPTION TO SATISFY THE RISING DEMAND FOR SUCH PRODUCTS FROM ALL CORNERS OF THE MARKET**

Installation Recommendations:

Dry installation is recommended. Please refer to the ReTac Clear PET Application Guide for more details.

For more information, performance and warranty guidelines please contact your local Drytac office.

© 2023 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATIONS

PRODUCT STRUCTURE

Film	Gloss Clear Polyester (PET)
Adhesive	Clear ReTac® ultra removable and repositionable adhesive technology
Release Liner	78# one side siliconized PE coated Kraft

PRODUCT CHARACTERISTICS

Film Thickness	3.0 mil (75µ)	3.7 mil (93µ)
Adhesive Layer	0.7 mil (18µ)	
Outdoor Durability	5 Years; 2 Years Removability (Ink Dependant)	
FDA Certification	PASS (FDA 21 CFR 177.1630(f).(g))	
Application Temperature	>41°F (5°C)	
Service Temperature Range	40°F to 120°F (4.4°C to 48.9°C)	
Shelf Life	2 Years	
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

