

Reveal™ Backlit Solvent

Print Media

Reveal™ Backlit Solvent is an 8.5 mil (215µ) high quality, printable gloss white PET backlit film that is specifically designed for illuminating graphics and clearly displaying messages. Its anti-static, anti-slip treatment on the back side keeps messages securely in place. The film disperses light evenly and consistently across images for vibrant graphic displays. It is front side printable and provides superb adhesion for (eco) solvent, UV and latex inks. It can be cut with large format CNC finishing systems. Reveal™ Backlit Solvent is distortion-free and comparable to durable transparency. Its brilliant white point yields excellent color saturation, tonal rendition and contrast for more vivid graphics.

Typical Applications

- Ideal choice for backlit graphics in airports, museums and malls.
- Can be used for outdoor backlit applications at bus stops or train stations.
- Rigidity allows graphics to be more easily inserted into light boxes.

Print Compatibility

- (Eco) Solvent
- Latex
- UV

Physical Characteristics

Film Thickness	8.5 mil (215µ)
Finish	Gloss
UV Protection Factor	Not Applicable
Outdoor Durability	2 years
Service Temperature Range	-40°F to 250°F (-40°C to 121°C)
Shelf Life	Use within 1 year after opening original box
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

IMPORTANT NOTE:

Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein.

Only the correct use of the product will allow satisfactory results. For this reason, Drytac is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Drytac at one of the phone numbers listed below.