

"L" SEALERS & TUNNEL COMBINATION



Specification	PPG 1519 MK	PPG 1622 MKA
Power Supply	220V/1 PH/20 amps	220V/3 PH/45 amps
Sealing Dimension	15"W × 19"L	16"W × 22"L
Sealing Device	Micro knife	
Maximum Film Width	18"	20"
Power Take Away Conveyor (variable speed)	YES	
Film Perforator	Included	
Pneumatic cycle	n/a	Included
Tunnel Opening	20"L × 16"W × 6"H	28"L × 18"W × 8"H
Machine Dimension	75"L × 26"W	103"L × 32"W
Shipping Weight	600 lbs.	950 lbs.

Standard Features Sealer

- ✚ Micro Knife Seal Blade
- ✚ Rugged Heavy Duty Frame
- ✚ Easy to Load Film Cradle with Brake
- ✚ Film Perforator
- ✚ Dual Magnet Clamping
- ✚ Locking Casters

Standard Features Tunnel

- ✚ Fully Re-Circulating Air Chamber
- ✚ Automatic Tunnel Cool Down with Shut Off
- ✚ Adjustable Air Velocity Control
- ✚ Digital Temperature Control
- ✚ Live Roller Rod Conveyor
- ✚ Locking Casters

pro pack group

DYNACLEAR® SHRINK FILM



THE COMPLETE SOURCE FOR YOUR PACKAGING NEEDS EQUIPMENT & SUPPLIES