

ViziPrint® UV

Print Media

ViziPrint® UV is a clear polyester film that is coated with an ink-receptive top coat, coated on the other side with a pressure sensitive, removable aqueous acrylic adhesive, which is protected by a micro-grooved release paper that imparts an embossed pattern into the adhesive coating.

Typical Applications

- Produced using a high quality polyester film that is printable by UV technology.
- The micro grooves imparted into the removable adhesive allow for easy air evacuation for applications onto glass, acrylic and other non-porous surfaces.
- The removable adhesive can be re-positioned up to 10 times with 24 hours of applying and can be cleanly removed within 12 months after application.
- Ideal for creating high quality graphics for retail store fronts, POP and backlit displays, as well as simple, quick applications such as posting a menu to a restaurant window.
- The image is reverse printed on the printable side, and if required, then backed with a white self-adhesive vinyl.

Product Structure

Film	Clear Polyester Coated with Ink-Receptive Top Coat	90µ (0.6 mil)
Adhesive	Removable Aqueous Acrylic (Pressure Sensitive)	
Release Liner	2 Side PE Coated Structured Release Paper	

Physical Characteristics

Film Thickness	75µ (3 mil)
Adhesive Layer	15µ (0.6 mil)
Ratio Film/Adhesive	5:1
UV Protection Factor	Not Applicable
Outdoor Durability	Not Applicable
Heat Resistance Range	70°C - 95°C (158°F - 203°F)
Peel Strength (24 hours, FTM1)	3 N/25mm

IMPORTANT NOTE:

Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein.

Only the correct use of the product will allow satisfactory results. For this reason, Drytac is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Drytac at one of the phone numbers listed below.